




- **Fail-silent failures**
 - subsystem either produces correct results or produces (recognizable) incorrect results or remains quiet
 - **can be masked as long as at least one system survives**
- **Consistent failures**
 - If subsystem produces incorrect results all recipients receive same (incorrect) result
 - **can be masked iff the failing systems form a minority**
- **Byzantine failures**
 - subsystem reports different results to different dependent systems
 - **can be masked iff strictly less than a third of the systems fail**

Dynamic hardware redundancy: standby spare arrangement

REVIEW




- Fault detection based on outputs (consistency check) not on voting
- Advantage: less redundant hardware
- Disadvantage: fault detection may take time \Rightarrow fault not masked

BF - ES

- 3 -

Static hardware redundancy: Multiple Stage TMR



REVIEW



BF - ES

- 4 -

Boeing 777



BF - ES

- 5 -


Reliability: $f(t)$, $F(t)$

REVIEW

- Let T : time until first failure, T is a random variable
- Let $f(t)$ be the density function of T

Example: Exponential distribution

$$f(t) = \lambda e^{-\lambda t}$$




- $F(t)$ = probability of the system being faulty at time t .

$$F(t) = \Pr(T \leq t) \quad F(t) = \int_0^t f(x) dx$$

Example: Exponential distribution

$$F(t) = \int_0^t \lambda e^{-\lambda x} dx = -[e^{-\lambda x}]_0^t = 1 - e^{-\lambda t}$$



BF - ES

- 6 -

Reliability: $R(t)$

REVIEW

- **Reliability** $R(t)$ = probability that the time until the first failure is larger than some time t .


$$R(t) = \Pr(T > t), t \geq 0 \quad R(t) = \int_t^{\infty} f(x) dx$$

$$F(t) + R(t) = \int_0^t f(x) dx + \int_t^{\infty} f(x) dx = 1$$

$$R(t) = 1 - F(t)$$

Example: Exponential distribution

$$R(t) = e^{-\lambda t}$$



BF - ES

- 7 -


Reliability block analysis

REVIEW

- **Goal:** compute reliability of a system from the reliability of its components
- **Serial composition**



- **Parallel composition**



BF - ES


- 8 -

Inductive computation of reliability

REVIEW


- **Assumption:** failures of the individual components are independent

- **Serial composition**



- **Parallel composition**

$$1 - \prod_{i=1}^N (1 - R_i(t))$$



BF - ES

- 9 -

Approximation: Minimal Cuts

REVIEW

- A **minimal cut** is a minimal set of components such that their simultaneous failure causes a system failure

- $1 - \sum_{j \in \text{MinimalCuts}} \prod_{i \in j} [1 - R_i(t)]$

is a lower bound for the reliability $R(t)$ of the full system.

- Minimal cuts with a single component are called *single point failures*.

BF - ES

- 10 -

Approximation: Minimal Tie Sets

- A **minimal tie set** is a minimal set of components such that their simultaneous functioning guarantees the functioning of the system


- $$\sum_{j \in \text{MinimalTies}} \prod_{i \in j} R_i(t)$$

is an upper bound for the reliability $R(t)$ of the full system.


BF - ES

- 11 -

Example




Minimal cuts:



$$R \geq 1 - [(1 - 0.5) + (1 - 0.5)^2] = 1 - [0.5 + 0.25] = 0.25$$

Minimal ties:



$$R \leq 0.5 \cdot (0.5 + 0.5 \cdot 0.5) = 0.5$$

BF - ES

$$\underline{\text{Exact:}} \quad 0.5 \cdot (1 - (1 - 0.5)^2) = 0.5 \cdot 0.75 = 0.375$$

Fault tree Analysis (FTA)


- FTA is a top-down method of analyzing risks. Analysis starts with possible damage, tries to come up with possible scenarios that lead to that damage.
- FTA typically uses a graphical representation of possible damages, including symbols for AND- and OR-gates.
- OR-gates are used if a single event could result in a hazard.
- AND-gates are used when several events or conditions are required for that hazard to exist.



BF - ES

- 13 -

Example: Brake fluid warning lamp



- 14 -

Direct Analysis

$$1 - \sum_{\vec{p} \in \{0,1\}^n} (FT(\vec{p}) \cdot \prod_{i=1}^n (1 - R_i(t))^{p_i} \cdot R_i(t)^{1-p_i})$$

where

$\vec{p} = (p_1, \dots, p_n)$ denotes the occurrence of the base events, and

$FT(\vec{p})$ denotes the value of the top event


Problem: combinatorial explosion!

BF - ES

- 15 -

Equivalence

- Two fault trees are equivalent if the associated logical formulas are equivalent.
- E.g., $(A \vee (B \vee C) \wedge (C \vee (A \wedge B))) \equiv (C \vee (A \wedge B))$



BF - ES

- 16 -


Minimal cut sets

Minimal cut set = “smallest set of basic events which, in conjunction, cause the top level event to occur”.

Logically: **Disjunctive Normal Form (DNF)** = disjunction of conjunctions of basic events.

Example:

C (single point of failure) and
 $A \wedge B$.




BF - ES

- 17 -

Mocus Algorithm (1972) „Method of Obtaining Cut Sets“

- Initialize the first element of a matrix with the top event operator
- As long as there is still an operator in the matrix:
 - If it is an AND operator, replace it with its inputs in the column
 - If it is an OR operator, replace it with its inputs in the row.
- Each column corresponds to a cut set; reduce to obtain minimal cut sets.



BF - ES

Nikolaos Limnios: *Fault Trees*

- 18 -

Example


$$[g_n] \rightarrow [g_2 \ g_3]$$

$$\rightarrow \begin{bmatrix} 1 & g_3 \\ g_4 & g_3 \end{bmatrix}$$

$$\rightarrow \begin{bmatrix} 1 & 2 \\ 1 & g_5 \\ g_4 & g_3 \end{bmatrix}$$

$$\rightarrow \begin{bmatrix} 1 & 2 \\ 1 & 3 \\ 1 & 4 \\ g_4 & g_3 \end{bmatrix}$$

\Rightarrow cut sets: $\{1,3,4\}, \{2,3,4\}$.



BF - ES


- 19 -

Binary decision trees

- Let X be a set of boolean variables and $<$ a total order on X
- **Binary decision tree** (BDT) is a complete binary tree over $\langle X, < \rangle$
 - each leaf v is labeled with a boolean value $val(v) \in \mathbb{B}$
 - non-leaf v is labeled by a boolean variable $Var(v) \in X$
 - such that for each non-leaf v and vertex w :

$$w \in \{left(v), right(v)\} \Rightarrow (Var(v) < Var(w) \vee w \text{ is a leaf})$$

\Rightarrow On each path from root to leaf, variables occur in the **same order**




BF - ES

- 20 -

Example

$$\text{BDT} = p_1 \wedge (\neg p_2 \vee p_3)$$



BF - ES

- 21 -

Shannon Expansion

- Each boolean function $f : \mathbb{B}^n \rightarrow \mathbb{B}$ can be written as:

$$f(x_1, \dots, x_n) = (x_i \wedge f[x_i := 1]) \vee (\neg x_i \wedge f[x_i := 0])$$

- where $f[x_i := 1]$ stands for $f(x_1, \dots, x_{i-1}, 1, x_{i+1}, \dots, x_n)$
- and $f[x_i := 0]$ is a shorthand for $f(x_1, \dots, x_{i-1}, 0, x_{i+1}, \dots, x_n)$

- The boolean function $f_B(v)$ represented by vertex v in BDT B is:

- for v a leaf: $f_B(v) = \text{val}(v)$
- otherwise:

$$f_B(v) = (\text{Var}(v) \wedge f_B(\text{right}(v))) \vee (\neg \text{Var}(v) \wedge f_B(\text{left}(v)))$$

- $f_B = f_B(v)$ where v is the root of B

BF - ES

- 22 -

Considerations on BDTs

- BDTs are **not compact**
 - a BDT for boolean function $f : \mathbb{B}^n \rightarrow \mathbb{B}$ has 2^n leafs
 - ⇒ they are as space inefficient as truth tables!
- ⇒ BDTs contain quite some **redundancy**
 - all leafs with value one (zero) could be collapsed into a single leaf
 - a similar scheme could be adopted for isomorphic subtrees
- The size of a BDT does not change if the variable order changes

BF - ES

- 23 -

Ordered Binary Decision Diagrams

share equivalent expressions [Akers 76, Lee 59]

- **Binary decision diagram** (OBDD) is a **directed graph** over $\langle X, < \rangle$ with:
 - each leaf v is labeled with a boolean value $val(v) \in \{0, 1\}$
 - non-leaf v is labeled by a boolean variable $Var(v) \in X$
 - such that for each non-leaf v and vertex w :

$$w \in \{left(v), right(v)\} \Rightarrow (Var(v) < Var(w) \vee w \text{ is a leaf})$$


- ⇒ An OBDD is acyclic
 - f_B for OBDD B is obtained as for BDTs

BF - ES

- 24 -

Example

$$p_1 \wedge (\neg p_2 \vee p_3)$$



BF - ES

- 25 -

Reduced OBDDs

OBDD B over $\langle X, < \rangle$ is called *reduced* iff:

1. for each leaf v, w : $(val(v) = val(w)) \Rightarrow v = w$

\Rightarrow identical terminal vertices are forbidden

2. for each non-leaf v : $left(v) \neq right(v)$


\Rightarrow non-leaves may not have identical children

3. for each non-leaf v, w :

$(Var(v) = Var(w) \wedge right(v) \cong right(w) \wedge left(v) \cong left(w)) \Rightarrow v = w$

\Rightarrow vertices may not have isomorphic sub-dags

this is what is mostly called BDD; in fact it is an ROBDD!



BF - ES

- 26 -

Canonicity

[Fortune, Hopcroft & Schmidt, 1978]

For ROBDDs B and B' over $\langle X, < \rangle$ we have:
 $(f_B = f_{B'})$ implies B and B' are isomorphic

\Rightarrow for a fixed variable ordering, any boolean function
can be uniquely represented by an ROBDD (up to isomorphism)

BF - ES

- 27 -

MakeNode(var, v₁, v₂)

If $H(\text{var}, v_1, v_2) \neq \text{empty}$ then return $H(\text{var}, v_1, v_2)$;

lookup in
hashtable

If $(v_1 = v_2)$ then return v_1

$\text{res} := \text{new node}(\text{var}, v_1, v_2)$;

$H(\text{var}, v_1, v_2) := \text{res}$;

memorize
result

return res;

BF - ES

- 28 -

Computing AND and OR

- Shannon expansion for binary operations:

$$f \text{ op } g = (x_1 \wedge (f[x_1 := 1] \text{ op } g[x_1 := 1])) \vee (\neg x_1 \wedge (f[x_1 := 0] \text{ op } g[x_1 := 0]))$$

- A **top-down evaluation** scheme using the Shannon's expansion:
 - let v be the variable highest in the ordering occurring in B_f or B_g
 - split the problem into subproblems for $v := 0$ and $v := 1$, and solve recursively
 - at the leaves, apply the boolean operator op directly
 - reduce afterwards to turn the resulting OBDD into an ROBDD
- Efficiency gain is obtained by **dynamic programming**
 - the time complexity of constructing the ROBDD of $B_f \text{ op } B_g$ is in $\mathcal{O}(|B_f| \cdot |B_g|)$

BF - ES

- 29 -

Apply(op, v₁, v₂)

```

if  $G(v_1, v_2) \neq \text{empty}$  then return  $G(v_1, v_2)$  fi;
if ( $v_1$  and  $v_2$  are terminals) then  $res := val(v_1) \text{ op } val(v_2)$  fi;
else if ( $v_1$  is terminal and  $v_2$  is nonterminal)
  then  $res := MakeNode(Var(v_2), APPLY(op, v_1, left(v_2)), APPLY(op, v_1, right(v_2)))$ ;
else if ( $v_1$  is nonterminal and  $v_2$  is terminal)
  then  $res := MakeNode(Var(v_1), APPLY(op, left(v_1), v_2), APPLY(op, right(v_1), v_2))$ ;
else if ( $Var(v_1) = Var(v_2)$ )
  then  $res := MakeNode(Var(v_1), APPLY(op, left(v_1), left(v_2)), APPLY(op, right(v_1), right(v_2)))$ ;
else if ( $Var(v_1) < Var(v_2)$ )
  then  $res := MakeNode(Var(v_1), APPLY(op, left(v_1), v_2), APPLY(op, right(v_1), v_2))$ ;
else
   $res := MakeNode(Var(v_2), APPLY(op, v_1, left(v_2)), APPLY(op, v_1, right(v_2)))$ ;
 $G(v_1, v_2) := res$ ;
return  $res$ 

```



lookup in
hashtable

memorize
result


BF - ES

- 30 -

Example



- Apply (λ, u_1, u_2)
- Apply (λ, u_2, u_2) ✓
- Apply (λ, u_2, u_2) ✓
- Apply ($\lambda, 0, 0$)
- Apply ($\lambda, 1, u_3$)
- Apply (λ, u_2, u_3)
- Apply ($\lambda, 0, u_3$) = 0
- Apply ($\lambda, 1, u_3$)
- Apply ($\lambda, 1, u_1$)



BF - ES

- 31 -


ROBDDs of Fault Trees

- Each path through the BDD from the root to a leaf node represents a disjoint combination of component failures and non-failures
- A path with a leaf node labeled with a 1 leads to system failure
- Probabilities associated with arcs on each path are either $(1-R(t))$ (component failure probability) for the right branch or $R(t)$ for the left branch
- System unreliability is given by the sum of the probabilities for all paths from the root to a leaf node labeled 1

BF - ES

- 32 -

Example




$$\begin{aligned} \Rightarrow R(t) &= \\ & (1 - R_1(t)) \cdot (1 - R_2(t)) \\ & + (1 - R_1(t)) \cdot R_2(t) \\ & \quad \cdot (1 - R_3(t)) \cdot (1 - R_4(t)) \\ & + R_1(t) \\ & \quad \cdot (1 - R_3(t)) \cdot (1 - R_4(t)) \end{aligned}$$

BF - ES

- 33 -

Recursive BDD evaluation



$$R(t) = R_x(t) * R_l(t) + (1 - R_x(t)) * R_r(t)$$


$$R_1(t) = 1$$

$$R_0(t) = 0$$

BF - ES

- 34 -

ROBDDs can be exponentially large




The ROBDD of $f_{stab}(\bar{x}, \bar{y}) = (x_1 \leftrightarrow y_1) \wedge \dots \wedge (x_n \leftrightarrow y_n)$
has $3 \cdot 2^n - 1$ vertices under ordering $x_1 < \dots < x_n < y_1 < \dots < y_n$

BF - ES

- 35 -

Alternative variable ordering



The ROBDD of $f_{stab}(\bar{x}, \bar{y}) = (x_1 \leftrightarrow y_1) \wedge \dots \wedge (x_n \leftrightarrow y_n)$
has $3 \cdot n + 2$ vertices under ordering $x_1 < y_1 < \dots < x_n < y_n$

BF - ES

- 36 -

Optimal variable ordering

- The size of ROBDDs is dependent on the variable ordering
- Is it possible to determine ϵ such that the ROBDD has minimal size?
 - the optimal variable ordering problem for ROBDDs is NP-complete
 - polynomial reduction from the 3SAT problem (Bollig & Wegener, 1996)
- There are many boolean functions with large ROBDDs
 - for almost all boolean functions the minimal size is in $\Omega(\frac{2^n}{n})$
- How to deal with this problem in practice?
 - guess a variable ordering in advance
 - rearrange the variable ordering during the manipulations of ROBDDs

BF - ES

- 37 -

Sifting Algorithm (1993)

Dynamic variable reordering using variable swapping

1. Select some variable x_i
2. By successive swapping determine position where the ROBDD has least size
3. Shift to its optimal position
4. Go back to 1 until no more improvement.

Often only yields local optimum, but works well in practice.

BF - ES

- 38 -

Limitations of combinatorial models

- Assumption that failure probability is independent of the system state is often wrong.

Example: cold-spare redundancy

- Failure during standby is unlikely
- Failure during activation is likely

⇒ state-based models are required