

## Embedded Systems

5



BF - ES

- 1 -

## Exam Dates / Registration

- **Midterm**, Thursday December 18, 2008, 16-18
- **Final**, Thursday February 12, 2009, 16-19
  
- Registration through **HISPOS** (open in approx. 1 week)
- (If HISPOS not applicable – Non-CS, Erasmus, etc – send email to [finkbeiner@cs.uni-sb.de](mailto:finkbeiner@cs.uni-sb.de))
  
- No separate course sign-up  
BUT: Please indicate tutorial, matr nr, name, e-mail on **homework submissions**.

BF - ES

- 2 -

## Petri Nets

## REVIEW

**Def.:**  $N=(C,E,F)$  is called a **Petri net**, iff the following holds


1.  $C$  and  $E$  are disjoint sets
2.  $F \subseteq (C \times E) \cup (E \times C)$ ; is binary relation, („**flow relation**“)

**Def.:** Let  $N$  be a net and let  $x \in (C \cup E)$ .

$\bullet x := \{y \mid y F x\}$  is called the set of **preconditions**.

$x^\bullet := \{y \mid x F y\}$  is called the set of **postconditions**.

**Competing Trains Example:**




BF - ES

- 3 -

## Boolean marking and computing changes of markings


## REVIEW

- A Boolean marking is a mapping  $M: C \rightarrow \{0,1\}$ .
- „Firing“ events  $x$  generate new markings on each of the conditions  $c$  according to the following rules:
  - a transition at  $x$  can be **fired**, iff  $\bullet x$ , i.e. all preconditions of  $x$  are marked and  $x^\bullet$  is not marked, after firing  $\bullet x$  is unmarked and  $x^\bullet$  is marked
- $M \rightarrow M'$ , iff  $M'$  results from  $M$  by firing exactly one transition



## Competing Trains Example is C/E net:

REVIEW



BF - ES

- 5 -

## Condition/event nets (C/E nets)

REVIEW

### Def.:

A Petri net  $N=(C,E,F)$  together with a set of markings  $M$  is called **condition/event net (C/E net)**, iff


- $N$  is simple and has no isolated elements
- $M$  is closed w.r.t. “firing” and “inverse firing”
- two markings in  $M$  can be transformed into each other by “firing” and “inverse firing”
- for each event  $e \in E$ , there exists a marking in  $M$ , that allows firing at  $e$

BF - ES

- 6 -

## Example Thalys trains: more complex

- Thalys trains between Cologne, Amsterdam, Brussels and Paris.
- Synchronization at Brussels and Paris




## Place/transition nets

**REVIEW**

**Def.:**  $(P, T, F, K, W, M_0)$  is called a **place/transition net (P/T net)** iff

- $N=(P, T, F)$  is a **net** with places  $p \in P$  and transitions  $t \in T$
- $K: P \rightarrow (\mathbb{N}_0 \cup \{\omega\}) \setminus \{0\}$  denotes the **capacity** of places ( $\omega$  symbolizes infinite capacity)
- $W: F \rightarrow (\mathbb{N}_0 \setminus \{0\})$  denotes the **weight of graph edges**
- $M_0: P \rightarrow \mathbb{N}_0 \cup \{\omega\}$  represents the **initial marking** of places




defaults:  
K =  $\omega$   
W = 1

In the following: assume initial marking is finite, capacity  $\omega$ .

BF - ES

- 8 -

## Example: Job processing system



BF - ES


- 9 -

## Computing changes of markings

## REVIEW

- „Firing“ transitions  $t$  generate new markings on each of the places  $p$  according to the following rules:

$$M'(p) = \begin{cases} M(p) - W(p,t), & \text{if } p \in \bullet t \setminus t^\bullet \\ M(p) + W(t,p), & \text{if } p \in t^\bullet \setminus \bullet t \\ M(p) - W(p,t) + W(t,p), & \text{if } p \in \bullet t \cap t^\bullet \\ M(p) & \text{otherwise} \end{cases}$$



BF - ES


- 10 -

## Activated transitions

## REVIEW

- Transition  $t$  is „activated“ iff

$$(\forall p \in \bullet t : M(p) \geq W(p,t)) \wedge (\forall p \in t^\bullet : M(p) + W(t,p) \leq K(p))$$



Activated transitions can „take place“ or „fire“, but don't have to.  
The order in which activated transitions fire is not fixed (it is non-deterministic).

BF - ES

- 11 -

## Shorthand for changes of markings

## REVIEW

Firing transition:

$$M'(p) = \begin{cases} M(p) - W(p,t), & \text{if } p \in \bullet t \setminus t^\bullet \\ M(p) + W(t,p), & \text{if } p \in t^\bullet \setminus \bullet t \\ M(p) - W(p,t) + W(t,p), & \text{if } p \in \bullet t \cap t^\bullet \\ M(p) & \text{otherwise} \end{cases}$$

Let

$$\underline{t}(p) = \begin{cases} -W(p,t) & \text{if } p \in \bullet t \setminus t^\bullet \\ +W(t,p) & \text{if } p \in t^\bullet \setminus \bullet t \\ -W(p,t) + W(t,p) & \text{if } p \in \bullet t \cap t^\bullet \\ 0 & \text{otherwise} \end{cases}$$

$$\Rightarrow \forall p \in P: M'(p) = M(p) + \underline{t}(p)$$

$$\Rightarrow M' = M + \underline{t} \quad +: \text{ vector add}$$

BF - ES

- 12 -


## Reachability relation

- $M [t > M'$  iff  $M' = M +_t$
- $M [\varepsilon > M'$  iff  $M = M'$
- $M [qt > M'$  iff  $\exists M'' . M [q > M''$  and  $M'' [t > M'$
- $M [* > M'$  iff  $\exists q . M [q > M'$
  
- **Reachability set**  $R(M) = \{M' \mid M [* > M'\}$
- **Reachability graph**  $RG(M)$ :  
nodes  $R(M)$ , edges  $\{(M, t, M') \mid M [t > M'\}$

BF - ES

- 13 -

## Unbounded Petri net



BF - ES

- 14 -

## Boundedness

- A place is **safe** if it contains at most one token in all reachable markings.
- A net is **safe** if all places are safe.
- A place is ***k*-bounded** if it contains at most *k* token in all reachable markings.
- A place is **bounded** if it is *k*-bounded for some *k*.
- A net is **bounded** if each place is bounded.

BF - ES

- 15 -

## Boundedness

**Theorem 1:** A P/T net (with finite initial marking) is bounded iff its reachability set is finite.

BF - ES

- 16 -

## Boundedness

**Theorem 2:** A P/T net is unbounded iff there exist two reachable markings  $M, M'$ , such that  $M \ll^* M'$  and  $M' > M$ .

BF - ES

- 17 -

## Proof of Theorem 2

**Lemma:** Every infinite sequence of markings  $(M_i)$  contains a weakly monotonically growing infinite subsequence  $(M'_i)$ , i.e., for  $j < k$ ,  $M'_j \leq M'_k$ .

BF - ES

- 18 -

## Proof of Theorem 2

BF - ES

- 19 -

## Algorithm for deciding boundedness

- Explore  $RG(M_0)$  depth-first:
  - If there exists a marking  $M'$  on the stack such that  $M' < M$ , stop with result UNBOUNDED;
- If entire graph explored, return BOUNDED.

BF - ES

- 20 -

## Weak Petri net computers


A P/T net with  
 $r$  distinguished input places ( $in_i$ ),  
 a finite number of internal places  $s_p$ ,  
 one extra output place ( $out$ ),  
 one extra start place ( $on$ ), and  
 one extra stop place ( $off$ )  
 is called a **weak Petri net computer** for the function  $f: \mathbb{N}^r \rightarrow \mathbb{N}$   
 iff there exists for each  $x \in \mathbb{N}^r$  an initial marking  $M_x$   
 such that

- $M_x(on)=1$  and  $M_x(in_i)=x_i$  for  $1 \leq i \leq r$ ;
- $M_x(out)=M_x(off)=0$ ;
- $M_x(s_p)=0$ ;
- For all reachable markings  $M \neq M_x$ ,  
 $M(on)=0$  and  $1 \leq M(off) \leq 1$  and  $M(out) \leq f(x)$ ;
- For all reachable markings  $M \neq M_x$ , if  $M(off)=1$  then  $M$  is dead;
- For all  $0 \leq k \leq f(x)$ , there exists a reachable marking  $M$   
 such that  $M(out)=k$  and  $M(off)=1$ .

BF - ES

- 21 -

## Addition




Source: Matthias Jantzen, Complexity of Place/Transition Nets (1986)

BF - ES

- 22 -

## Multiplication



Source: Matthias Jantzen, Complexity of Place/Transition Nets (1986)

BF - ES

- 23 -

## $RG(M_0)$ is not primitive recursive

### Proofidea:

Let  $A(n): \mathbb{N} \rightarrow \mathbb{N}$  be defined by  $A(n) = A_n(2)$

- $A_0(m) = 2m + 1$
- $A_{n+1}(0) = 1$
- $A_{n+1}(m+1) = A_n(A_{n+1}(m))$

$A(0) = 5; A(1) = 7; A(2) = 15; A(3) = 65535; \dots$

$A(n)$  majorizes the primitive recursive functions.


We can implement  $A(n)$  as a P/T net (that grows slowly with  $n$ ).

Source: Matthias Jantzen, Complexity of Place/Transition Nets (1986)

BF - ES

- 24 -


$$A_0(m) = 2m + 1$$



BF - ES

- 25 -

$$g(m+1) := f(g(m)), g(0) = f(0)$$




BF - ES

- 26 -




## Example Liveness



BF - ES

- 29 -

## Example Liveness



BF - ES

- 30 -

## Reversibility

- A P/T net is **reversible**  
iff for every  $M \in R(M_0)$ ,  $M \xrightarrow{*} M_0$
- **Theorem 3:** In a reversible net, a transition  $t$  is live  
iff  $t$  is not dead in  $M_0$ .

## Computation of Invariants

We are interested in subsets  $R$  of places whose number of labels remain invariant under transitions,


- e.g. the number of trains commuting between Amsterdam and Paris (Cologne and Paris) remains constant

Important for correctness proofs, e.g. the proof of liveness

BF - ES

- 33 -

## Competing Trains Example: Place Invariant 2,0,-2



BF - ES

- 34 -

## Shorthand for changes of markings

## REVIEW

Firing transition:

$$M'(p) = \begin{cases} M(p) - W(p,t), & \text{if } p \in \bullet t \setminus t \bullet \\ M(p) + W(t,p), & \text{if } p \in t \bullet \setminus \bullet t \\ M(p) - W(p,t) + W(t,p), & \text{if } p \in \bullet t \cap t \bullet \\ M(p) & \text{otherwise} \end{cases}$$

Let

$$\underline{t}(p) = \begin{cases} -W(p,t) & \text{if } p \in \bullet t \setminus t \bullet \\ +W(t,p) & \text{if } p \in t \bullet \setminus \bullet t \\ -W(p,t) + W(t,p) & \text{if } p \in \bullet t \cap t \bullet \\ 0 & \end{cases}$$

$$\Rightarrow \quad \forall p \in P: M'(p) = M(p) + \underline{t}(p)$$

$$\Rightarrow \quad M' = M + \underline{t} \quad \text{+ : vector add}$$

BF - ES

- 35 -

## Matrix $\underline{N}$ describing all changes of markings

## REVIEW

$$\underline{t}(p) = \begin{cases} -W(p,t) & \text{if } p \in \bullet t \setminus t \bullet \\ +W(t,p) & \text{if } p \in t \bullet \setminus \bullet t \\ -W(p,t) + W(t,p) & \text{if } p \in \bullet t \cap t \bullet \\ 0 & \end{cases}$$

Def.: Matrix  $\underline{N}$  of net  $N$  is a mapping

$$\underline{N}: P \times T \rightarrow Z \text{ (integers)}$$

such that  $\forall t \in T: \underline{N}(p,t) = \underline{t}(p)$


Component in column  $t$  and row  $p$  indicates the change of the marking of place  $p$  if transition  $t$  takes place.

BF - ES

- 36 -

## Example: $\underline{N} =$

## REVIEW



- 37 -

## Characteristic Vector

$$\sum_{p \in R} t_{-j}(p) = 0$$

Let: 
$$\underline{c}_R(p) = \begin{cases} 1 & \text{if } p \in R \\ 0 & \text{if } p \notin R \end{cases}$$

$$\Rightarrow \sum_{p \in R} t_{-j}(p) = t_{-j} \cdot \underline{c}_R = \sum_{p \in P} t_{-j}(p) \underline{c}_R(p) = 0$$

↑  
Scalar product

BF - ES

- 38 -

## Condition for place invariants

$$\sum_{p \in R} t_j(p) = \underline{t}_j \cdot \underline{c}_R = \sum_{p \in P} t_j(p) \underline{c}_R(p) = 0$$

Accumulated marking constant for **all** transitions if

$$\begin{aligned} \underline{t}_1 \cdot \underline{c}_R &= 0 \\ \dots &\dots \dots \\ \underline{t}_n \cdot \underline{c}_R &= 0 \end{aligned}$$

Equivalent to  $\underline{N}^T \underline{c}_R = \mathbf{0}$  where  $\underline{N}^T$  is the transposed of  $\underline{N}$

BF - ES

- 39 -

## More detailed view of computations

$$\begin{pmatrix} t_1(p_1) \dots t_1(p_n) \\ t_2(p_1) \dots t_2(p_n) \\ \dots \\ t_m(p_1) \dots t_m(p_n) \end{pmatrix} \begin{pmatrix} c_R(p_1) \\ c_R(p_2) \\ \dots \\ c_R(p_n) \end{pmatrix} = \begin{pmatrix} 0 \\ 0 \\ 0 \\ 0 \end{pmatrix}$$


System of linear equations.

Solution vectors must consist of zeros and ones.

BF - ES

- 40 -

## Competing Trains Example



BF - ES

- 41 -